查询N74F251AD供应商

8-input multiplexer (3-State) 74F251A

FEATURES

- High speed 8-to-1 multiplexing
- On chip decoding
- Multifunction capability
- Inverting and Non-Inverting outputs
- Both outputs are 3-State for further multiplexer expansion

DESCRIPTION

The 74F251A is a logic implementation of a single 8-position switch with the switch position controlled by the state of three Select (S0, S1, S2) inputs. True (Y) and complementary ($\overline{Y}$) outputs are both provided. The output enable ($\overline{OE}$) is active Low. When $\overline{OE}$ is High, both outputs are in High impedance state, allowing multiple output connections to a common bus without driving nor loading the bus significantly. All but one device must be in High impedance state to avoid high currents that would exceed the maximum ratings when the outputs of the 3-State devices are tied together. When the output of more than one device is tied together the user must ensure that there is no overlap in the active Low portion of the output enable voltages.

PIN CONFIGURATION



TYPE	TYPICAL PROPAGATION DELAY	TYPICAL SUPPLY CURRENT (TOTAL)
74F251A	4.5ns	19mA

ORDERING INFORMATION

DESCRIPTION	ORDER CODE	PKG DWG #
	COMMERCIAL RANGE V_{CC} = 5V ±10%, T_{amb} = 0°C to +70°C	
16-pin plastic DIP	N74F251AN	SOT38-4
16-pin plastic SO	N74F251AD	SOT162-1

INPUT AND OUTPUT LOADING AND FAN-OUT TABLE

PINS	DESCRIPTION	74F (U.L.) HIGH/LOW	LOAD VALUE HIGH/LOW
I0–I7	Data inputs	1.0/1.0	20µA/0.6mA
S0–S2	Select inputs	1.0/1.0	20µA/0.6mA
$\overline{OE}$	Output Enable input (active Low)	1.0/1.0	20µA/0.6mA
Y, $\overline{Y}$	Data outputs	150/40	3mA/24mA

NOTE:
One (1.0) FAST unit load is defined as: 20µA in the High state and 0.6mA in the Low state.

LOGIC SYMBOL



IEC/IEEE SYMBOL



LOGIC DIAGRAM



FUNCTION TABLE

INPUTS				OUTPUTS	
S2	**S1**	**S0**	**$\overline{OE}$**	**Y**	**$\overline{Y}$**
X	X	X	H	Z	Z
L	L	L	L	I0	$\overline{I0}$
L	L	H	L	I1	$\overline{I1}$
L	H	L	L	I2	$\overline{I2}$
L	H	H	L	I3	$\overline{I3}$
H	L	L	L	I4	$\overline{I4}$
H	L	H	L	I5	$\overline{I5}$
H	H	L	L	I6	$\overline{I6}$
H	H	H	L	I7	$\overline{I7}$

NOTES:
H = High voltage level
L = Low voltage level
X = Don't care
Z = High impedance "off" state

ABSOLUTE MAXIMUM RATINGS

(Operation beyond the limit set forth in this table may impair the useful life of the device.
Unless otherwise noted these limits are over the operating free air temperature range.)

SYMBOL	PARAMETER	RATING	UNIT
V_{CC}	Supply voltage	–0.5 to +7.0	V
V_{IN}	Input voltage	–0.5 to +7.0	V
I_{IN}	Input current	–30 to +5	mA
V_{OUT}	Voltage applied to output in High output state	–0.5 to V_{CC}	V
I_{OUT}	Current applied to output in Low output state	48	mA
T_{amb}	Operating free-air temperature range	0 to +70	°C
T_{stg}	Storage temperature	–65 to +150	°C

RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5.0	5.5	V
V_{IH}	High-level input voltage	2.0			V
V_{IL}	Low-level input voltage			0.8	V
I_{IK}	Input clamp current			–18	mA
I_{OH}	High-level output current			–3	mA
I_{OL}	Low-level output current			24	mA
T_{amb}	Operating free-air temperature range	0		70	°C

DC ELECTRICAL CHARACTERISTICS

(Over recommended operating free-air temperature range unless otherwise noted.)

SYMBOL	PARAMETER		TEST CONDITIONS[1]		LIMITS			UNIT
					MIN	TYP[2]	MAX	
V_{OH}	High-level output voltage		V_{CC} = MIN, V_{IL} = MAX, V_{IH} = MIN, I_{OH} = MAX	±10%V_{CC}	2.4			V
				±5%V_{CC}	2.7	3.3		V
V_{OL}	Low-level output voltage		V_{CC} = MIN, V_{IL} = MAX, V_{IH} = MIN, I_{OL} = MAX	±10%V_{CC}		0.35	0.50	V
				±5%V_{CC}		0.35	0.50	V
V_{IK}	Input clamp voltage		V_{CC} = MIN, I_I = I_{IK}			–0.73	–1.2	V
I_I	Input current at maximum input voltage		V_{CC} = MAX, V_I = 7.0V				100	µA
I_{IH}	High-level input current		V_{CC} = MAX, V_I = 2.7V				20	µA
I_{IL}	Low-level input current		V_{CC} = MAX, V_I = 0.5V				–0.6	mA
I_{OZH}	Off-state output current High-level voltage applied		V_{CC} = MAX, V_I = 2.7V				50	µA
I_{OZL}	Off-state output current Low-level voltage applied		V_{CC} = MAX, V_I = 0.5V				–50	mA
I_{OS}	Short-circuit output current[3]		V_{CC} = MAX		–60		–150	mA
I_{CC}	Supply current (total)	I_{CCH}	V_{CC} = MAX			20	27	mA
		I_{CCL}				17	24	mA
		I_{CCZ}				21	29	mA

NOTES:
1. For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.
2. All typical values are at V_{CC} = 5V, T_{amb} = 25°C.
3. Not more than one output should be shorted at a time. For testing I_{OS}, the use of high-speed test apparatus and/or sample-and-hold techniques are preferable in order to minimize internal heating and more accurately reflect operational values. Otherwise, prolonged shorting of a High output may raise the chip temperature well above normal and thereby cause invalid readings in other parameter tests. In any sequence of parameter tests, I_{OS} tests should be performed last.

AC ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER	TEST CONDITION	LIMITS					UNIT
			V_{CC} = +5V T_{amb} = +25°C C_L = 50pF R_L = 500Ω			V_{CC} = +5V ± 10% T_{amb} = 0°C to +70°C C_L = 50pF R_L = 500Ω		
			MIN	TYP	MAX	MIN	MAX	
t_{PLH} t_{PHL}	Propagation delay In to Y	Waveform 2	3.0 3.0	5.0 5.0	7.0 7.0	2.5 3.0	8.0 8.0	ns
t_{PLH} t_{PHL}	Propagation delay In to $\overline{Y}$	Waveform 1	2.5 1.0	4.5 2.5	7.0 5.0	2.0 1.0	7.5 5.0	ns
t_{PLH} t_{PHL}	Propagation delay Sn to Y	Waveform 1 Waveform 2	4.5 4.0	6.5 5.5	10.0 9.0	4.0 3.5	11.5 9.5	ns
t_{PLH} t_{PHL}	Propagation delay Sn to $\overline{Y}$	Waveform 1 Waveform 2	3.5 2.5	6.0 4.5	9.0 7.0	3.5 2.5	9.5 7.5	ns
t_{PZH} t_{PZL}	Output Enable time $\overline{OE}$ to Y	Waveform 3 Waveform 4	3.5 3.5	5.5 5.0	7.5 7.5	3.0 3.0	8.5 8.0	ns
t_{PHZ} t_{PLZ}	Output Disable time $\overline{OE}$ to Y	Waveform 3 Waveform 4	2.5 1.0	4.0 4.0	6.5 6.0	2.0 1.0	7.0 6.5	ns
t_{PZH} t_{PZL}	Output Enable time $\overline{OE}$ to $\overline{Y}$	Waveform 3 Waveform 4	2.5 2.5	4.0 4.0	6.5 6.5	2.0 2.5	7.0 7.0	ns
t_{PHZ} t_{PLZ}	Output Disable time $\overline{OE}$ to $\overline{Y}$	Waveform 3 Waveform 4	3.5 1.0	5.0 2.0	7.5 4.5	3.0 1.0	8.0 4.5	ns

AC WAVEFORMS

For all waveforms, V_M = 1.5V



Waveform 1. For Inverting Outputs



Waveform 2. For Non-Inverting Outputs



Waveform 3. 3-State Output Enable Time to High Level and Output Disable Time from High Level



Waveform 4. 3-State Output Enable Time to Low Level and Output Disable Time from Low Level

TEST CIRCUIT AND WAVEFORMS



Test Circuit for 3-State Outputs



Input Pulse Definition

SWITCH POSITION

TEST	SWITCH
t_{PLZ}	closed
t_{PZL}	closed
All other	open

DEFINITIONS:

R_L = Load resistor; see AC electrical characteristics for value.

C_L = Load capacitance includes jig and probe capacitance; see AC electrical characteristics for value.

R_T = Termination resistance should be equal to Z_{OUT} of pulse generators.

family	INPUT PULSE REQUIREMENTS					
	amplitude	V_M	rep. rate	t_w	t_{TLH}	t_{THL}
74F	3.0V	1.5V	1MHz	500ns	2.5ns	2.5ns

SF00777